

Gel based concrete stripper - For Professional Use Only

Description

Avista Concrete Sealer Stripper is a gel based stripper that can be used to remove both solvent and waterbased sealers from concrete surfaces. Its penetrating performance allows for multiple layers of sealer to be stripped in a single application. NOTE: This product should only be used by professional contractors.

Uses

Avista Concrete Sealer Stripper can be used to strip both waterbased and solvent sealers from internal and external concrete surfaces including resurfaced areas.

Advantages

- Safer choice for indoor use, does not contain Methylene Chloride (MC) or N-Methyl Pyrrolidone (NMP)
- Strips multiple coating layers in one application
- Water clean up

Properties

Colour:	Translucent pale Yellow
Active Ingredients:	Dimethyl Sulfoxide, Dibasic Ester
Shelf Life:	24 months
Strip Time (approx):	Water Based: 15-20 min. Solvent Bases: 60 min.
Coverage	0.5m ² /L when applied 2mm thick on horizontal surface

*Indicative data only, not intended for preparation of specifications

Application Instructions

1. Apply Avista Stripper approximately 2mm thick to the concrete surface with a long nap roller or paint brush.
2. Allow stripper to stand. Stripping times may vary according to the number of sealer layers, age and type. As a guide, water based coatings begin to soften after 15-20 minutes. Allow 1 hour for solvent based sealers. Note that the stripper remains effective while in a wet state so do not allow the stripper to dry on the surface.

Important notice

A Safety Data Sheet (SDS) and Technical Data Sheet (TDS) are available from the Parchem website or upon request from the nearest Parchem sales office. Read the SDS and TDS carefully prior to use as application or performance data may change from time to time. In emergency, contact any Poisons Information Centre (phone 13 11 26 within Australia) or a doctor for advice.

Product disclaimer

This Technical Data Sheet (TDS) summarises our best knowledge of the product, including how to use and apply the product based on the information available at the time. You should read this TDS carefully and consider the information in the context of how the product will be used, including in conjunction with any other product and the type of surfaces to, and the manner in which, the product will be applied. Our responsibility for products sold is subject to our standard terms and conditions of sale. Parchem does not accept any liability either directly or indirectly for any losses suffered in connection with the use or application of the product whether or not in accordance with any advice, specification, recommendation or information given by it.

3. Pressure clean the surface at a minimum 2000psi to remove the stripper and sealer. Ensure the run off is collected and disposed of in accordance with local authority requirements.
Note: To prevent 'Wash Off' from entering drains, dam both ends of gutter with sandbags. Place a slurry or similar pump at the lowest point. Pump waste into a drum for disposal.
4. Should any sealer remain on the surface, repeat the steps above.
5. Allow the surface to dry completely before starting the resealing process.

Clean up

Clean tools with water.

Handy hints

By placing builders plastic over the area to be stripped will reduce evaporation and give more effective stripping.

Limitations

Ensure gutters and kerbs are protected to local council standards.

Supply

178017 AVS SEALER STRIPPER 20L

Storage

Store in a cool, dry area and keep container sealed.

Shelf life

Two (2) years, if kept in unopened container and stored in cool, dry conditions. After this time, the product should be checked for its suitability for use.

Add SAFETY

Recommended PPE:

- Organic vapour respirator mask
- Solvent resistance gloves
- Safety eye wear
- Appropriate foot wear